

Issued by : NMI Certin B.V.
Thijssseweg 11
2629 JA Delft
The Netherlands

Applicant : SATEC Ltd.
10 Milltown Court Union
NJ 07083
Unites States of America

Submitted : **A meter embedding IEC 61000-4-30 class A Power Quality functions**

Manufacturer : Satec LTD
Type : PM335, EM235, EM 720 PRO, PM17X

Characteristics : See page 2 and further

In accordance with : **IEC 61000-4-30:2015+AMD1:2021**
"Electromagnetic Compatibility (EMC) – Part 4-30: Testing and measurement techniques – Power quality measurement methods"
IEC 62586-2:2017+AMD1:2020
"Power quality measurement in power supply systems - Part 2: Functional tests and uncertainty requirements"

Measurement class : IEC 61000-4-30 class A

The undersigned declares that the described product is tested according to the above mentioned standard and meets their requirements, based on a non-recurrent examination. The appertaining test data is presented in type evaluation report number NMI-3694152-01, granted by NMI Certin B.V.

NMI Certin B.V.
5 September 2024

Certification Board

NMI Certin B.V.
Thijssseweg 11
2629 JA Delft
The Netherlands
T +31 88 636 2332
certin@nmi.nl
www.nmi.nl

This document is issued under the provision that no liability is accepted and that the applicant shall indemnify third-party liability.

Reproduction of the complete document only is permitted.

This document is digitally signed and sealed. The digital signature can be verified in the blue ribbon at the top of the electronic version of this certificate.

IEC 61000-4-30 Power Quality functions tested

The following IEC 61000-4-30 measurement methods have been tested

Table 1 IEC 61000-4-30 Power Quality functions tested

IEC 62586-2 Clause	Parameter	IEC 61000-4-30 class	Comments
6.1 / 7.1	Power frequency	A	50 and 60 Hz
6.2 / 7.2	Magnitude of supply voltage	A	
6.3 / 7.3	Flicker	A	Class F1 230V, 50 Hz
6.4 / 7.4	Supply voltage interruptions, dips and swells	A	50 and 60 Hz
6.5 / 7.5	Supply voltage unbalance	A	
6.6 / 7.6	Voltage harmonics	A	
6.7 / 7.7	Voltage interharmonics	A	
6.8 / 7.8	Mains signalling voltages on the voltage supply	A	Method 2
6.9 / 7.9	Measurement of underdeviation and overdeviation parameters	-----	Not implemented
6.10 / 7.10	Flagging	A	
6.11 / 7.11	Clock uncertainty testing	A	
6.12 / 7.12	Variation of external influence quantities	A	Temperature: -25°C ..+ 55°C Power supply: 88 – 277 VAC
6.13 / 7.13	Rapid Voltage Changes (RVC)	A	
6.14 / 7.14	Magnitude of current	A	
6.15 / 7.15	Harmonic current	A	
6.16 / 7.16	Interharmonic currents	A	
6.17 / 7.17	Current unbalance	A	
8	Calculation of measurement uncertainty and operating uncertainty	A	

A : compliance with class A
S : compliance with class S
--- : Not implemented

The tests are performed in accordance with IEC 62586-2 edition 2 (2017).

Characteristics of the measuring instrument

In Table 2 the general characteristics of the measuring instrument are presented.

Table 2 General characteristics

Model	EM235, PM335, PM17X PRO, EM720 PRO
U_{din}	230 V _{LN}
I_{nom}	5 A
f_{nom}	50 Hz and 60 Hz
Temperature	Rated range of operation: 0°C to +55°C
Power supply range	88-264V AC, 50/60 Hz 40-290 VDC VDC
Software version	V44.XX
VN.2	VN.2
Environmental application	Fixed (F), Indoor (I)